



# Material Safety Data Sheet

## TRISERT<sup>®</sup> K<sup>+</sup>, 5-0-20

MSDS Number 75600 (Revised: 5/6/02)

6 Pages

<b>Section 1: CHEMICAL PRODUCT and COMPANY IDENTIFICATION</b>
---

- 1.1 Product Name** ..... **Trisert<sup>®</sup> K<sup>+</sup>, 5-0-20**  
Chemical Family ..... Aqueous, organic salt solution  
Synonyms ..... Potassium thiosulfate, Urea Triazone and urea  
Formula ..... N/A - blend
- 1.2 Manufacturer** ..... **Tessenderlo Kerley Inc.**  
2255 N. 44<sup>th</sup> Street, Suite 300  
Phoenix, Arizona 85008-3279  
Information ..... (602) 889-8300
- 1.3 Emergency Contact** ..... (800) 877-1737 (Tessenderlo Kerley)  
**(800) 424-9300 (CHEMTREC)**

<b>Section 2: COMPOSITION, INFORMATION ON INGREDIENTS</b>
---

**2.1 Chemical Ingredients (% by wt.)**

TRISERT<sup>®</sup>-K<sup>+</sup> is a proprietary blend of Urea Triazone, urea and Potassium Thiosulfate solution (KTS<sup>®</sup>).

(See Section 8 for exposure guidelines)

<b>Section 3: HAZARDS IDENTIFICATION</b>
--

**NFPA:**      **Health - 1**      **Flammability - 0**      **Reactivity - 0**

<p style="text-align: center;"><b>EMERGENCY OVERVIEW</b></p> <p>Contact with solution or mist may cause eye irritation. Repeated/prolonged skin contact with solution or mist may cause irritation. Ingestion may irritate gastrointestinal tract. Excessive heating may cause ammonia gas to evolve.</p>
---

<b>Section</b>	<b>3:</b>	<b>HAZARDS IDENTIFICATION (Cont.)</b>
----------------	-----------	---------------------------------------

### 3.1 POTENTIAL HEALTH EFFECTS

**EYE:** Contact with the eyes by product mist or solution may cause irritation or a burning sensation.

**SKIN CONTACT:** Prolonged or repeated contact with product mist or solution may cause skin irritation.

**SKIN ABSORPTION:** Absorption is unlikely to occur.

**INGESTION:** Ingestion of product solution may cause irritation of the gastrointestinal tract to include nausea, vomiting and diarrhea. These blends are considered to have a low toxicity to humans.

**INHALATION:** Inhalation of product mist may cause irritation of the nose, throat and respiratory tract.

**CHRONIC EFFECTS/CARCINOGENICITY:** Not listed as a carcinogen by NTP, IARC or OSHA.

<b>Section</b>	<b>4:</b>	<b>FIRST AID MEASURES</b>
----------------	-----------	---------------------------

**4.1 EYES:** Immediately flush with large quantities of water for 15 minutes. Hold eyelids apart during irrigation to insure thorough flushing of the entire area of the eye and lids. Obtain medical attention.

**4.2 SKIN:** Immediately flush with large quantities of water. Remove contaminated clothing under a safety shower. Obtain medical attention if irritation occurs.

**4.3 INGESTION:** If victim is conscious, give 2 to 4 glasses of water and induce vomiting by touching finger to back of throat. Obtain medical attention.

**4.4 INHALATION:** Remove victim from contaminated atmosphere. If breathing is labored, administer oxygen. If breathing has ceased, clear airway and start mouth to mouth resuscitation. If heart has stopped beating, external heart massage should be applied. Obtain medical attention.

<b>Section</b>	<b>5:</b>	<b>FIRE FIGHTING MEASURES</b>
----------------	-----------	-------------------------------

### 5.1 FLAMMABLE PROPERTIES

**FLASH POINT:** Not flammable

**METHOD USED:** NA

### 5.2 FLAMMABLE LIMITS

**LFL:** NA

**UFL:** NA

**5.3 EXTINGUISHING MEDIA:** As appropriate for combustibles involved in fire.

**5.4 FIRE & EXPLOSIVE HAZARDS:** Heating to dryness may cause the release of ammonia and carbon dioxide.

**5.5** Keep containers/storage vessels in fire area cooled with water spray. Intense heating may cause the release of ammonia vapors.

<b>Section</b>	<b>5:</b>	<b>FIRE FIGHTING MEASURES (Cont.)</b>
----------------	-----------	---------------------------------------

**5.5 FIRE FIGHTING EQUIPMENT:** As in any fire, wear self-contained breathing apparatus, pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

<b>Section</b>	<b>6:</b>	<b>ACCIDENTAL RELEASE MEASURES</b>
----------------	-----------	------------------------------------

**6.1 Small releases:** Confine and absorb small releases on sand earth or other inert absorbent. Use water spray to dilute to weak fertilizer solution.

**6.2 Large releases:** Confine area to qualified personnel. Shut off release if safe to do so. Dike spill area to prevent runoff into sewers, drains or surface waterways (potential aquatic toxicity). Recover as much of the solution as possible. Treat remaining material as a small release (above).

<b>Section</b>	<b>7:</b>	<b>HANDLING and STORAGE</b>
----------------	-----------	-----------------------------

**7.1 Handling:** Avoid contact with eyes. Use only in a well ventilated area. Wash thoroughly after handling. Avoid prolonged or repeated breathing of vapors. Avoid prolonged or repeated contact with the skin.

**7.2 Storage:** Store in well ventilated areas. Do not store combustibles in the area of storage vessels. Keep away from any sources of heat or flame. Store tote and smaller containers out of direct sunlight at moderate temperatures [less than 105°F (41°C)] but greater than 0°F (-17.8°C). (See Section 10.4 for materials of construction)

<b>Section</b>	<b>8:</b>	<b>EXPOSURE CONTROLS, PERSONAL PROTECTION</b>
----------------	-----------	---

**8.1 RESPIRATORY PROTECTION:** None generally required. If conditions exist where mist may be generated, a NIOSH/MSHA approved mist respirator should be worn.

**8.2 SKIN PROTECTION:** Neoprene rubber gloves and apron should be worn to prevent repeated or prolonged contact with the liquid. Wash contaminated clothing prior to reuse.

**8.3 EYE PROTECTION:** Chemical goggles and a full face shield

**8.4 EXPOSURE GUIDELINES:**

	OSHA		ACGIH	
	<u>TWA</u>	<u>STEL</u>	<u>TLV</u>	<u>STEL</u>
None	N/A	NA	NA	NA

**8.5 ENGINEERING CONTROLS:** Use adequate exhaust ventilation to prevent inhalation of product vapors.

**Section 9: PHYSICAL and CHEMICAL PROPERTIES**

<b>9.1 APPEARANCE:</b>	Clear, light green-brown liquid
<b>9.2 ODOR:</b>	May have a slight amine odor
<b>9.3 BOILING POINT:</b>	Not determined
<b>9.4 VAPOR PRESSURE:</b>	Not Determined
<b>9.5 VAPOR DENSITY:</b>	Not determined
<b>9.6 SOLUBILITY IN WATER:</b>	Complete
<b>9.7 SPECIFIC GRAVITY:</b>	1.4 (11.66 lbs/gal)
<b>9.8 MELTING POINT:</b>	Salt out temperature less than 10° F (-12°C)
<b>9.9 pH:</b>	9 to 12
<b>9.10 VOLATILE:</b>	Not applicable

**Section 10: STABILITY and REACTIVITY**

**10.1 STABILITY:** This is a stable material

**10.2 HAZARDOUS POLYMERIZATION:** Will not occur

**10.3 HAZARDOUS DECOMPOSITION PRODUCTS:** Heating to dryness will cause the production of ammonia, and oxides of carbon.

**10.4 INCOMPATIBILITY:** Strong oxidizers such as nitrates, nitrites or chlorates can cause explosive mixtures if heated to dryness. Avoid contact with Acids or acid materials. This product may not be compatible with copper, zinc or their alloys (i.e. bronze, brass, galvanized metals, etc.). These materials of construction should not be used in piping, handling systems or storage containers for this product. (SEE Section 7.2, Storage)

**Section 11: TOXICOLOGICAL INFORMATION**

**11.1 ORAL:** Data not available

**11.2 DERMAL:** Data not available

**11.3 INHALATION:** Data not available

**11.4 CHRONIC/CARCINOGENICITY:** No evidence available

**11.5 TERATOLOGY:** Data not available

**11.6 REPRODUCTION:** Data not available

**11.7 MUTAGENICITY:** Data not available

**Section 12: ECOLOGICAL INFORMATION**

No data available.

<b>Section</b>	<b>13:</b>	<b>DISPOSAL CONSIDERATIONS</b>
----------------	------------	--------------------------------

The product TRISERT®-K<sup>+</sup> is not considered hazardous waste under Federal Hazardous Waste Regulations, 40 CFR 261. Consult state and local regulations for more restrictive disposal regulations.

<b>Section</b>	<b>14:</b>	<b>TRANSPORT INFORMATION</b>
----------------	------------	------------------------------

<b>14.1 DOT Shipping Name:</b>	Potassium thiosulfate, triazone and urea fertilizer solution
<b>14.2 DOT Hazard Class:</b>	NA
<b>14.3 UN/NA Number:</b>	NA
<b>14.4 Packing Group:</b>	NA
<b>14.5 DOT Placard:</b>	NA
<b>14.6 DOT Label(s):</b>	NA
<b>14.7 IMO Shipping Name:</b>	Potassium thiosulfate, triazone and urea fertilizer solution
<b>14.8 RQ (Reportable Quantity):</b>	NA
<b>14.9 RR STCC Number:</b>	Unknown

<b>Section</b>	<b>15:</b>	<b>REGULATORY INFORMATION</b>
----------------	------------	-------------------------------

<b>15.1 OSHA:</b>	This product is listed as a hazardous material under criteria of the Federal OSHA Hazard Communication Standard, 29 CFR 1910.1200.	
<b>15.2 SARA TITLE III:</b>	a.	<b>EHS</b> (Extremely Hazardous Substance) List: No
	b.	Section 311/312, (Tier I,II) Categories: Immediate (acute) Yes Fire No Sudden release No Reactivity No Delayed (chronic) No
	c.	Section 313 (Toxic Release Reporting-Form R): No
		<u>Chemical Name</u> <u>CAS Number</u> <u>Concentration</u> NA
	d.	<b>TPQ</b> (Threshold Planning Quantity): No
<b>15.3 CERCLA/SUPERFUND:</b>	RQ (Reportable Quantity)	No
<b>15.4 TSCA</b> (Toxic Substance Control Act) Inventory List:		Yes

**Section 15: REGULATORY INFORMATION (Cont.)**

<b>15.5 RCRA</b> (Resource Conservation and Recovery Act) Status:	NA
<b>15.6 WHMIS</b> (Canada) Hazard Classification:	NA
<b>15.7 DOT</b> Hazardous Material: (See Section 14)	No
<b>15.8 CAA</b> Hazardous Air Pollutant (HAP)	No

**Section 16: OTHER INFORMATION**

**REVISIONS:** The entire MSDS was reformatted to comply to ANSI Standard Z400.1-1993, by Technical Services-Tessengerlo Kerley, Inc.

Revised Section 8.3, Eye Protection, and company logo, 5/6/02

THE INFORMATION PUBLISHED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN COMPILED FROM OUR EXPERIENCE AND OSHA, ANSI, NFPA, DOT, ERG, AND CHRIS. IT IS THE USER'S RESPONSIBILITY TO DETERMINE THE SUITABILITY OF THIS INFORMATION FOR THE ADOPTION OF NECESSARY SAFETY PRECAUTIONS. WE RESERVE THE RIGHT TO REVISE MATERIAL SAFETY DATA SHEETS PERIODICALLY AS NEW INFORMATION BECOMES AVAILABLE.